

Universal Joint Selection

To select a part number start by using the Universal Joint prefix of "401-"next choose either "5" for single black oxide, "3" for single stainless, "6" for single chrome finish, "8" for double black oxide and "9" for double chrome. Follow with the combination of yokes you would like, starting with the lowest number first.

Example:
401-50615 = Standard 3/4" Smooth x 3/4"-30

#	Description	Finish
6	3/4" Smooth Bore	---
7	5/8"-36 Spline, Mini Rack / Stiletto	---
8	5/8" Smooth Bore	---
9	Heidts Aftermarket Ford R&P	---
10	3/4"-48 Spline, Sweet Spline	---
11	13/16"-36 Spline, Chevy Power	---
12	3/4"-36 Spline, Pinto Power, Quickener	==
13	9/16"-26 Spline Pinto Manual	---
14	5/8"-36 Spline, Vega Box	---
15	3/4"-30 Spline, NCP, Sweet Int. Rack	---
17	Corvette Bottom Set Screw	---
17	Corvette Top Set Screw	---
18	1"-48 Spline, Stock GM Column	---
19	3/4" Double "D"	==
20	1" Double "D" OEM Column	---
21	3/4"-20 Spline, Sweet Column	---
23	1" Double "D" IDIDIT Column	---
24	Jeep Flat	---
27	OEM Ford Rack and Pinion 1994 & Up	---
28	19mm -17 Spline	---
29	Allied Motion EPAS	---
30	5/8"-36 Spline, Flaming River Vega Box	---
32	7/8" Smooth Bore with Key-way	---
33	19mm -24 R-Max	---
34	19/32"-29 Spline, Yamaha Rhino	---
35	19/32" Smooth Bore	---
36	1/2" Smooth Bore	---
37	11/16"-36 Spline	---
73	23mm-20 Spline	---
74	Jeep Flat Pincher	---
75	16.5mm-36 Spline	---

Finish/Material Chrome — Stainless Steel —

6 $\phi 0.75$

7 5/16-24 Tapped Hole
5/8" - 36 Spline
.620" Major Diameter

8 $\phi 0.625$

9 0.74
5/16-24 Tapped Hole
0.391
 $\phi 0.75$
0.335

10 5/16-24 Tapped Hole
3/4" - 48 Spline

11 5/16-24 Tapped Hole
13/16" - 36 Spline

12 5/16-24 Tapped Hole
3/4" - 36 Spline

13 5/16-24 Tapped Hole
9/16" Spline

14 5/16-24 Tapped Hole
5/8" - 36 Spline
.600" Major Diameter

15 5/16-24 Tapped Hole
3/4" - 30 Spline

16 0.573
5/16-24 Tapped Hole
0.260
0.387
 $\phi 0.662$

17 0.573
 $\phi 0.662$
0.260
0.387
5/16-24 Tapped Hole

18 5/16-24 Tapped Hole
1" - 48 Spline

19 0.552
 $\phi 0.750$
0.508
5/16-24 Tapped Hole

20 0.800
 $\phi 0.985$
0.131
5/16-24 Tapped Hole
0.575
0.131
5/16-24 Tapped Hole

21 5/16-24 Tapped Hole
3/4" - 20 Spline

23 0.800
 $\phi 1.000$
0.131
5/16-24 Tapped Hole
0.600
0.131

24 0.610
 $\phi 0.735$
0.432
0.387
5/16-24 Tapped Hole

27 $\phi .739$
.678
5/16-24 Tapped Hole for Set-Screw

28 5/16"-24 TAPPED HOLE
 $\phi .676$ THRU
 $\phi .674$ THRU
3/4" x 17 SPLINE
EPowerSteering

29

30 5/16-24 Tapped Hole
5/8" - 36 Spline
.605" Major Diameter

32 0.185 Keyway
 $\phi 0.875$
 $\phi 0.325$ Thru Hole

33

34 5/16-24 Tapped Hole
19/32" - 29 Spline

35 5/16-24 Tapped Hole
 $\phi 0.594$

36 5/16-24 Tapped Hole
 $\phi 0.500$

37 5/16-24 Tapped Hole
11/16" - 29 Spline

73 5/16-18 Pinch Bolt
23mm-20 Spline

74 0.410
0.425
 $\phi 0.735$
0.610
1/4-28 Pinch Bolt

75 5/16-24 TAPPED HOLE
16.5mm 36 Spline

